PB-218 396

EXHAUST EMISSIONS FROM A REACTOR EQUIPPED, FULL-SIZED AUTOMOBILE USING LPG FUEL

John C. Thomson

Environmental Protection Agency
Ann Arbor, Michigan

March 1971

DISTRIBUTED BY:

NTIS

National Technical Information Service
U. S. DEPARTMENT OF COMMERCE
5285 Port Royal Road, Springfield Va. 22151

APTD-1422

71-21

PB 218 396

Exhaust Emissions From a Reactor Equipped, Full-Sized Automobile Using LPG Fuel

March 1971

Reproduced by
NATIONAL TECHNICAL
INFORMATION SERVICE
U S Department of Commerce
Springfield VA 22151

John C. Thomson
Division of Emission Control Technology
Mobile Source Pollution Control Program
Air Pollution Control Office
ENVIRONMENTAL PROTECTION AGENCY

BIBLIOGRAPHIC DATA SHEET	1. Report No. APTD-1422	2.	3. Recipient's Accession No. PB-218 396
4. Title and Subtitle: Exhaust Emissions from a Reactor Equipped, Full-Sized Automobile Using LPG Fuel			5. Report Date: March 1971 6.
7. Author(s): John C. Thomson			8. Performing Organization Rept. No.
9. Performing Organization Name and Address: ENVIRONMENTAL PROTECTION AGENCY Division of Emission Control Technology Ann Arbor, Michigan			10. Project/Task/Work Unit No. 11. Contract/Grant No.
12. Sponsoring Organization Name and Address: Same			13. Type of Report & Period Covered: Inhouse 14.

15. Supplementary Notes

16. Abstracts

Evaluations were made on a specially equipped 1971 Oldsmobile Delta 88. This vehicle was to have very low exhaust emissions, approaching the 1975 levels. A Century LPG Conversion Kit was used with modifications to provide low emissions. Also, a reactor, exhaust gas recycle and a pulse air injection system were supplied. The tests conducted were as follows: (1) standard 1970 Federal Test Procedure for exhaust emissions (FTP); (2) closed, constant volume sampling technique using nine repeats of the Federal emissions test cycle (9X7); (3) closed, constant volume sampling technique using the LA4-S4 driving schedule for 1972 and later testing. The results, which are tabulated indicate that the vehicle showed low emission levels. There were no attempts to measure driveability except for acceleration runs.

17. Key Words and Document Analysis. 17a. Descriptors

Air pollution
Automobile
Exhaust emissions
Fuels
Liquified petroleum gases
Conversion
Tests
Standards
Sampling
Carbon monoxide
Carbon dioxide
Nitrogen oxides
Hydrocarbons

17b. Identifiers/Open-Ended Terms

Federal Test Procedure (1970)
Constant Volume Sampling Technique
LA4-S4 driving schedule

17c. COSATI Field/Group 13B

18. Availability Statement: Unlimited	19. Security Class (This Report) UNCLASSIFIED	21. No. of Pages 6
	20. Security Class (This Page) UNCLASSIFIED	22. Price $3.00/$0.95

Vehicle Tested

A specially equipped 1971 Oldsmobile Delta 88 was supplied by General Motors for evaluation by APCO. This vehicle was to have very low exhaust emissions, approaching the 1975 levels. A Century LPG Conversion Kit was used with modifications made to provide low emissions. In addition, a reactor, exhaust gas recycle and a pulse air injection system were supplied. All vehicle tests were made using the fuel supplied by GM and no attempt was made to analyze the fuel composition.

Tests Conducted

The following tests were performed on the vehicle:

1. Standard 1970 Federal test procedure for exhaust emissions (FTP).

2. Closed, constant volume sampling technique using nine repeats of the Federal emissions test cycle (9x7).

3. Closed, constant volume sampling technique using the LA4-S4 driving schedule as developed for 1972 and later new vehicle certification (LA4).

Bag samples taken during closed cycle tests were analyzed using non-dispersive infrared analysis (IR) for carbon monoxide and carbon dioxide, flame ionization detection (FID) was used for hydrocarbon analysis. In order to compare oxides of nitrogen measurements with data taken on other vehicles, a variety of techniques were used. A modified Saltzman (Saltz) technique was used for wet chemical analysis, a chemiluminescent technique (CI), and an electrochemical (ENVTS) technique were also used. All results are reported as NO_2 and have been corrected for humidity using the following:

$$NO_2 \text{ corr} = \frac{NO_2 \text{ measured}}{1-0.0047\ (H-75)}$$

where H is the humidity in grains of water.

When open cycle tests were run, non-dispersive infrared oxides of nitrogen data were taken.

Emission Results

All of the data taken during the test period can be found in Tables 1 and 2. After the first test shown in Table 1, the carburetor was adjusted to improve driveability. The hydrocarbon values were consistantly higher than the proposed 1975 standards of 0.46 gpm while carbon monoxide was lower than the standard of 4.7 gpm except on the last test. No standard for oxides of nitrogen has been adopted, however, the values shown on these tests are very low. The hydrocarbon values would probably be reduced if a density for hydrocarbon in the exhaust had been determined and used in place of the standard density for gasoline. The results fell in the low ranges of the instruments used and the exact numbers may be questionable, although repeatability was good. Background hydrocarbon levels were quite high on some tests and may have influenced levels also.

Conclusions

The vehicle showed low emission levels. There were no attempts to measure driveability except for acceleration runs.

Table 1

Date	HC (FID)	CO (NDIR)	CO_2 (NDIR)	NO_x (Saltz)	NO_x (CI)	NO_x (ENVTS)
			LA4-S4 Test Results (gpm) *			
2/09	1.0	1.3	984	0.3	0.4	0.6
2/11	1.0	2.9	952	0.4	0.4	0.8
2/16	0.6	5.0	981	0.4	0.1	---
			9x7 Test Results			
2/12	0.6	1.4	905	0.6	0.2	0.6

* Results obtained using HC density of 16.33 and no correction for reactivity or fuel composition. The effect of density correction would be less than 10%.

TABLE 2

1970 Federal Test Procedure (FTP)*

Cycle	HC ppm	CO ppm	NO ppm
1	280	0.08	92
2	61	0.02	100
3	44	0.02	106
4	36	0.02	100
6	45	0.02	100
7	40	0.01	102
Composite	.93 gpm	.61 gpm	.45 gpm

* Results obtained using standard method with no correction for fuel type, reactivity or instrument response.